

LOYE cork floors

CORK-CORE

TECHNICAL INFORMATION

Technical data for the CORK-CORE range – Hydrocork – is shown below.

HYDROCORK TECHNICAL DATA

CHARACTERISTIC	STANDARD	RESULT
PHYSICALS		
Gauge	BS EN ISO 24346	6mm
Wear Layer	BS EN ISO 24340	0.55mm
Plank Size	BS EN ISO 24342	195 x 1225mm
Box Size		1.672M ²
Weight	BS EN ISO 23997	8.67kgs/M ²
PERFORMANCE		
General Performance	BS EN 14085	Conforms
Use area classification	BS EN ISO 10874	23 Domestic Heavy 33 Commercial Heavy
Indentation Residual	BS EN ISO 24343-1	≤ 0.1
Dimensional Stability	BS EN 669	≤ 5%
Colour Fastness	ISO 105-B02	≥ 6
Castor Chair	BS EN 425/ISO 4918	No visible change/damage after 25,000 cycles
Impact sound reduction	BS EN ISO 10140-3	16dB
SAFETY		
Reaction to fire	BS EN 13501-1	Bfl s1
Slip resistance	BS EN 13893	DS
ENVIRONMENTAL		
Formaldehyde Emission	BS EN 717-1	E1
Content of PCP	BS EN 14041 (annex B)	Undetectable
BREEAM		7 Points
VOC Emissions	AgBB	Very low emissions
	UL Greenguard	Gold
	French VOC regulation	A+

LOYE cork floors

CORK-CORE

- ❶ PROTECTIVE WEAR LAYER
- ❷ HIGH RESOLUTION DECORATIVE FILM
- ❸ SOLID VINYL LAYER
- ❹ CORK COMPOSITE CORE
- ❺ BALANCING VINYL LAYER



0330 055 3094 lovecorkfloors.com

